

# NUAGE®

## ANTIQUÉ EFFECT DECORATIVE FINISH BASED ON NATURAL OXIDES

### PRODUCT PROPERTIES

---

NUAGE is a very high quality, decorative product, formulated with acrylic resins in an aqueous emulsion with natural pigments and specific additives which give it the following properties:

GOOD BREATHABILITY, GOOD RESISTANCE TO WASHING WITH THE MOST COMMON DETERGENTS, GOOD IMPACT RESISTANCE AND GOOD RESISTANCE TO LIGHT.

The product is supplied in a neutral colour and can be coloured using Toners or the S2K Tinting system.

### USES

---

NUAGE is suitable for decorating interior walls. It gives a high quality, antique effect, decorative finish.

In addition, a variety of decorative effects can be obtained depending on the method of application used.

### TECHNICAL SPECIFICATIONS

---

**SPECIFIC WEIGHT:**

1.00 - 1.08 kg/l.

**VISCOSITY OF SUPPLY:**

6,000 - 15,000 cPs at 23°C.

**THEORETICAL COVERAGE PER COAT:**

100 g/m<sup>2</sup>, which varies according to the desired finish.

**APPEARANCE AND FINISH:**

Matt appearance, smooth finish.

**VOC (VOLATILE ORGANIC COMPOUND) EMISSION LIMIT:**

EU VOC limit value (Directive 2004/42/EU) for this product (Cat. A/I; BA): 300 g/l (2007); 200 g/l (2010).

NUAGE contains less than 200g/l VOC.

### METHOD OF USE

---

**SURFACE PREPARATION:**

ON NEW WALLS: brush down, fill holes and cracks and apply a coat of appropriately diluted PRIMER UNIFORMANTE A.S. (masking primer).

After 3-4 hours, apply one or two coats of FONDO AS. When this is dry, apply the NUAGE finish using brush strokes across an area of about 2 m<sup>2</sup> at a time.

ON PREVIOUSLY PAINTED WALLS: Remove all sections which are peeling and then proceed as for new walls.

**APPLICATION:**

Apply NUAGE finish using the appropriate brush.

After about 30 minutes, smooth the product down with the special flexible spatula exerting a slight pressure to obtain the desired aesthetic effect.

**DILUTION:**

Ready to use; may be diluted with clean water if necessary.

**DRYING TIME AT 20°C AND 65% RH:**

Dust dry after about 2 hours, fully dry after about 24 hours. Fifteen days are required for the product to dry completely and develop resistance to washing.

**ENVIRONMENTAL CONDITIONS:**

The product should be applied at environmental and/or surface temperatures of between 5°C and 30°C.

**WARNING:**

Mix the product manually to avoid breaking up the particles.

**CLEANING OF EQUIPMENT:**

Clean with water immediately after use.

---

**PACK SIZES:**

6 x 1.25L - 2 x 2.5L - 2 x 5L.

**AVAILABLE COLOURS:**

Neutral and as in the colour chart.

The product can be coloured using Toners or S2K Tinting System.

**SHELF LIFE AND STORAGE:**

The product will keep for at least 18 months from the date of purchase if stored in a cool, dry, frost-free location.

**NOTE:**

This document has been prepared to the best of our scientific and technical knowledge.

The company, Di Donato SpA, does not accept any responsibility for the results obtained with this product as the conditions and methods of application are beyond our control.

We therefore recommend that you check the product is suitable for your intended purpose before use.

